



# TECHNICAL DATA

# 1654

Classification:

- Lo pH Presoak

Product Description and Purpose:

- **Fire** is a concentrated high foaming Lo pH lubricating detergent that helps accelerate drying.

Features/Benefits:

- Excellent foamer
- Excellent cleaner
- Neutralizes residual alkalinity
- Brightens chrome
- Economizes drying agents
- Applicable through foamers or spray arches or cloth applications
- Free rinsing
- Biodegradable

Surfaces Applicable:

- All exterior auto services

General Usage Directions:

- Conveyor Foamer: 75:1 to 120:1. Use at 1/4 – 1 ounces per car.
- Conveyor Cloth Lube: 150:1 to 300:1.
- Automatic Presoak: 75:1 to 100:1. Use at 1 to 1 ½ ounces per car.

Titration Procedure:

- Fill clean plastic test tube to the 5-ml mark with application solution
- Add 3 drops of Indicator. No color change will occur.
- Add 0.5N NaOH titration solution drop by drop. Invert between drops until solution turns pink.

Caution:

- Keep out of reach of children. Keep container tightly closed when not in use. Protect from freezing. For industrial use only. Read Material Safety Data Sheet for more information.

Physical Properties:

- |                    |           |
|--------------------|-----------|
| • Form             | Liquid    |
| • Color            | Clear     |
| • Odor             | None      |
| • pH               | 1.0-2.0   |
| • Specific Gravity | 0.95-1.50 |
| • Boiling Point    | >212°F    |

Package Sizes & Numbers

- 4 X 1 Gallon Case 1654-B4
- 2 X 2.5 Gallon Case 1654-C5
- 5 gal 1654-B5
- 15 gal 1654-D15
- 30 gal 1654-D30
- 55 gal 1654-D55

