

AWE

TECHNICAL DATA

2291

Classification:

- Lo pH Presoaks

Product Description and Purpose:

- Lo pH liquid presoak containing detergents, specialty solvents and emulsifiers that gently penetrate and loosen the most difficult road soils and oils for quick and complete removal.

Features/Benefits:

- Highly concentrated, economical to use
- Safe on all surfaces
- Stable in hard water
- Non-spotting, won't dry out on hot cars
- Special solvents, cuts oil based soils.

Surfaces Applicable:

- All exterior auto services.

General Usage Directions:

- CONVEYOR FOAMER: 75:1 to 120:1.
Use at ¼ - 1 oz per car.
- AUTOMATIC PRESOAK: 90:1 to 120:1.
Use at 1 to 1 ½ oz per car.

Caution:

Keep out of reach of children. Keep container tightly closed when not in use. Protect from freezing. For industrial use only. Read Material Safety Data Sheets for more information.

Physical Properties:

- Form Liquid
- Color Light blue
- Odor Chemical
- Foam High
- pH 1.0-3.0
- Specific Gravity 1.00-1.05
- Boiling Point 212°F

Titration Procedure:

- Fill clean plastic test tube to the 5-ml mark with application solution.
- Add 3 drops of Indicator. No color change will occur.
- Add 0.5N NaOH titration solution drop by drop. Invert between drops until solution turns pink.

Package Sizes & Product Numbers:

- 2 x 2.5 gal case 2291-C5
- 5 gal 2291-B5
- 15 gal 2291-D15
- 30 gal 2291-D30
- 55 gal 2291-D55



CK Enterprises, Inc.