

# Supersonic

## Tech Data

**1071**

### Supersonic Tech Data Info

#### Classification:

- Low pH Presoaks

#### Product Description and Purpose:

• **Supersonic** is a very highly concentrated low pH liquid presoak that is a safer alternative to HF. Contains detergents, specialty solvents and emulsifiers that gently penetrate and loosen the most difficult road soils and oils for quick and complete removal.

#### Features/Benefits:

- Environmentally friendly
- Very highly concentrated
- Economical to use
- Safe on all surfaces
- Stable in hard water
- Special solvents, cuts oil based soils.

#### Surfaces Applicable:

- All exterior auto services.

#### General Usage Directions:

- CONVEYOR FOAMER: 120:1 to 240:1. Use at ¼ - ½ oz per car.
- AUTOMATIC PRESOAK: 120:1 to 240:1. Use at ½ to ¾ oz per car.

#### Caution:

Keep out of reach of children. Keep container tightly closed when not in use. Protect from freezing. For industrial use only. Read Material Safety Data Sheets for more information.

#### Physical Properties:

- Form
- Color
- Odor
- pH
- Specific Gravity
- Boiling Point

#### Titration Procedure:

- Fill clean plastic test tube to the 5-ml mark with application solution.
- Add 3 drops of Indicator. No color change will occur.
- Add 0.5N NaOH titration solution drop by drop. Invert between drops until solution turns pink.

#### Package Sizes & Numbers:

- 1 gal 1071-B4
- 2.5 gal 1071-C5
- 5 gal 1071 B5
- 30 gal 1071-D30



**CK Enterprises, Inc.**