

**ENERGY**

# BOLT PLUS

## TECHNICAL DATA

**1652****Classification:**

- Lo pH Presoak

**Product Description and Purpose:**

- **BOLT PLUS** is a super concentrated high foaming low pH lubricating detergent. Helps accelerate drying.

**Features/Benefits:**

- Super concentrated
- Excellent foamer
- Excellent cleaner
- Neutralizes residual alkalinity
- Brightens chrome
- Economizes drying agents
- Applicable through foamers or spray arches or cloth applications
- Free rinsing
- Biodegradable

**Surfaces Applicable:**

- All exterior auto services.

**General Usage Directions:**

- **CONVEYOR FOAMER:** 150:1 to 240:1. Use at ¼ - ½ ounces per car.
- **CONVEYOR CLOTH LUBE:** 300:1 to 600:1.
- **AUTOMATIC PRESOAK:** 150:1 to 366:1. Use at ¼ to ½ ounces per car.

**Caution:**

Keep out of reach of children. Harmful if swallowed. Avoid contact with skin, eyes, mucous membranes.

Wear rubber gloves, goggles, and protective clothing when handling product. Keep container tightly closed when not in use. Protect from freezing. For industrial use only. Read Material Safety Data Sheets for more information.

**Titration Procedure:**

- Fill clean plastic test tube to the 5-ml mark with application solution.
- Add 3 drops of Indicator. No color change will occur.
- Add 0.5N NaOH titration solution drop by drop. Invert between drops until solution turns pink.

**Physical Properties:**

- |                    |                |
|--------------------|----------------|
| • Form             | Liquid         |
| • Color            | Blue           |
| • Odor             | Slightly sweet |
| • Foam             | High           |
| • pH               | 0-1            |
| • Specific Gravity | 1.195-1.205    |
| • Boiling Point    | 219°F          |

**Package Sizes & Product Numbers:**

- 4x1 case 1652-B4
- 2x2.5 case 1652-C5
- 5 gal 1652-B5

**CK Enterprises, Inc.**