

**ENERGY**

ZIP

TECHNICAL DATA

8341**Classification:**

- High pH Presoak

Product Description and Purpose:

- **Zip** is a high foaming non-caustic high pH presoak that penetrates and loosens bug residues and road film. May be used in prep areas, as presoak shampoo, as well as touch free in-bay automatic wash applications.

Features/Benefits:

- Effective: Special blend of ingredients quickly penetrates & loosens soils
- Versatile: Can be used in a variety of applications
- High Foaming: Covers the car in copious amounts of foam

Surfaces Applicable:

- All Exterior Surfaces

General Usage Directions:

- Use at 128 to 200:1 and apply using low pressure

Caution:

Keep out of reach of children. Keep container tightly closed when not in use. Protect from freezing. For industrial use only. Read Material Safety Data Sheets for more information.

Titration Procedure:

- Fill clean plastic test tube to the 5-ml mark with application solution.
- Add 3 drops of Indicator. Solution should turn pink.
- Add 0.5N HCl titration solution drop by drop. Invert between drops until solution turns clear.

Physical Properties:

- | | |
|--------------------|--------------------------|
| • Form | Liquid |
| • Color | Blue |
| • Odor | Characteristic Soap Odor |
| • Foam | High |
| • pH (Conc.) | 12.5-13.5 |
| • Specific Gravity | 1.2-1.25 |
| • Boiling Point | 212°F |

Package Sizes & Product Numbers:

- 5 gal 8341-B5
- 15 gal 8341-D15
- 30 gal 8341-D30
- 55 gal 8341-D55

**CK Enterprises, Inc.**