

BOLT

TECHNICAL DATA

1651

Classification:

- Lo pH Presoak

Product Description and Purpose:

- **BOLT** is a concentrated high foaming pH lubricating detergent that helps accelerate drying.

Features/Benefits:

- Excellent foamer
- Excellent cleaner
- Neutralizes residual alkalinity
- Brightens chrome
- Economizes drying agents
- Applicable through foamers or spray arches or cloth applications
- Free rinsing
- Biodegradable

Surfaces Applicable:

- All exterior auto services.

General Usage Directions:

- **CONVEYOR FOAMER:** 75:1 to 120:1.
Use at ¼ - 1 ounces per car.
- **CONVEYOR CLOTH LUBE:** 150:1 to 300:1.
- **AUTOMATIC PRESOAK:** 75:1 to 100:1.
Use at 1 to 1 ½ ounces per car.

Caution:

Keep out of reach of children. Harmful if swallowed. Avoid contact with skin, eyes, mucous membranes. Wear rubber gloves, goggles, and protective clothing when handling product. Keep container tightly closed when not

in use. Protect from freezing. For industrial use only. Read Material Safety Data Sheets for more information.

Titration Procedure:

- Fill clean plastic test tube to the 5-ml mark with application solution.
- Add 3 drops of Indicator. No color change will occur.
- Add 0.5N NaOH titration solution drop by drop. Invert between drops until solution turns pink.

Physical Properties:

- Form Liquid
- Color Red
- Odor Slightly sweet
- Foam High
- pH 0.8-1.0
- Specific Gravity 1.115
- Boiling Point 219°F

Package Sizes & Product Numbers:

- 1 gal - 1651-B4
- 5 gal - 1651-B5
- 15 gal - 1651-D15
- 30 gal - 1651-D30
- 55 gal - 1651-D55

