



POWER BLEND

TUNNEL PRESOAK

TECH DATA

2161

Classification:

- Powerblend

Product Description and Purpose:

- **Power Blend Tunnel Presoak** is a super concentrated surfactant that is to be used as part of a two step frictionless system. Specifically designed for presoaks in a tunnel carwash

Features/Benefits:

- SUPER Concentrated
- Advanced Polymer European Surfactant Technology
- Melts Bugs and Removes Windshield Eyebrows

General Usage Directions:

- Draw with your choice Powerblend Foundation in a two part process. **Power Blend Tunnel Presoak** should be used with a tan 36" capillary tube. Total usage per car should be 4 – 8 ml

Caution:

Keep out of reach of children. Keep container tightly closed when not in use. Protect from freezing. For industrial use only. Read Safety Data Sheets for more information.

Physical Properties:

- | | |
|--------------------|---------------|
| • Form | Liquid |
| • Color | Straw / Amber |
| • Odor | Almond |
| • Foam | High |
| • pH | 1.5-2.5 |
| • Specific Gravity | 0.97 – 0.99 |
| • Boiling Point | 212° |

Package Sizes & Product Numbers:

- 4x1 case 2161-B4
- 5 gal 2161-B5
- 2x2.5 case 2161-C5
- 15 gal 2161-D15
- 55 gal 2161-D55



CK Enterprises, Inc.